


MV – MANUAL AIR VENT



Manual Air Vent with brass body, knurled operator with screwdriver slot, blowout-proof stem, and side discharge vent. Rated to 400 PSI (2760 kPa) and 250°F (120°C).

MODEL	NPT CONN	A		B		WRENCH SIZE	WEIGHT	
		in	mm	in	mm		lbs	kg
MV-025	.25"	1.75	44	0.62	16	9/16"	0.80	0.04




EV – EXTENDED MANUAL AIR VENT



Extended Manual Air Vent with brass body, knurled operator with screwdriver slot, blowout-proof stem, and side discharge vent. Rated to 400 PSI (2760 kPa) and 250°F (120°C).

MODEL	NPT CONN	A		B		WRENCH SIZE	WEIGHT	
		in	mm	in	mm		lbs	kg
EV-025	.25"	1.75	44	0.62	16	9/16"	0.80	0.04




AV – AUTOMATIC AIR VENT / CHECK-VALUE



Automatic air vent with brass body, plastic float, brass seat, and EPDM seal. Rated to 150 PSI (1035 kPa) and 240°F (115°C).

MODEL	NPT CONN		A		B		C		D		E		WRENCH SIZE		WEIGHT	
			in	.25"	3.62"	1.56"	.50"	2.62"	7/8"	.31	0.14	lbs	kg			
AV-025	.25"	in	.25"	3.62"	1.56"	.50"	2.62"	7/8"	.31	0.14						
		mm	6.35	92	40	13	66	22								



DV – DRAIN VALVE



Drain Valve with forged brass body, chrome plated ball, Teflon seats, double EPDM O-ring stem seals, aluminum handle, 3/4" hose connection with cap and plastic retainer strap. Rated to 600 PSI (4140 kPa) WOG and 250°F (120°C).

MODEL	NPT CONN	A		B		C		WEIGHT	
		in	mm	in	mm	in	mm	lbs	kg
DV-025	.25"	1.72	44	2.04	52	1.37	35	0.30	0.13
DV-050	.50"	2.45	62	2.77	70	1.46	37	1.46	0.65

