


No ATCV, 2.0" or smaller, Automatic Balanced, Strainer Supply, Components: SVe & ABe & 2x HA\*/FHT



### MODEL ABe

ABe Automatic Balancing Valve is a combination ball valve, automatic flow control device and union. The removable flow cartridge limits GPM to within  $\pm 5\%$  of specified flow. Fixed End connection available in FNPT or SWT. Tailpiece connection available in MNPT, FNPT or SWT. Size reductions available. Standard features include Adjustable Memory Stop and Dual Pressure/ Temperature Ports.

### MODEL SVe

SVe Combination Strainer Valve is a combination ball valve, wye strainer and union. The 20 mesh S/S strainer screen is removable for cleaning. Fixed End connection available in FNPT or SWT. Tailpiece connection available in MNPT, FNPT or SWT. Size reductions available. Standard features include Pressure/Temperature Port, Hose End Drain Valve and plugged Bypass Port.

### 2x MODEL HA

HA Direct Connect Hose Assemblies offer a direct connection to Valves and Coil Connection Components. Double crimp Stainless Steel ferrules over SS outer braiding with EPDM Rubber Liner. Brass cone seat swivel end with MNPT or SWT adapter. Hose Assembly lengths available in 18", 24" and 36". UL-94 V-0 Flame Resistant Rating.

QUANTITY	SIZE	GPM	TAG