


3-Way ATCV on Return, (Normally Open Mixing), 2.0" or smaller, Manual Balanced, Strainer Supply, Components: SVe, BBe, UB & MBe



MODEL MBe

MBe Manual Balancing Valve is a venturi balancing and shut off valve. Accuracy $\pm 3\%$ of flow rate. Fixed End connection available in FNPT or SWT. Tailpiece connection available in MNPT, FNPT or SWT. Size reductions available. Standard features include Adjustable Memory Stop and Dual Pressure/Temperature Ports.

MODEL SVe

SVe Combination Strainer Valve is a combination ball valve, wye strainer and union. The 20 mesh S/S strainer screen is removable for cleaning. Fixed End connection available in FNPT or SWT. Tailpiece connection available in MNPT, FNPT or SWT. Size reductions available. Standard features include Pressure/Temperature Port, Hose End Drain Valve and plugged Bypass Port.

MODEL UB

UB Union is an O-ring sealed union with two 0.25" plugged accessory ports. Fixed End Connections available in FNPT or SWT. Tailpiece Connections available in MNPT, FNPT or SWT. Size reductions available. Shown with "PV" Combination Manual Air Vent and Pressure/ Temperature Port.

MODEL BBe

BBe Union End Ball Valve is a throttling and shut off valve. Fixed End connection available in FNPT or SWT. Tailpiece connection available in MNPT, FNPT and SWT. Size reductions available. Standard features include Adjustable Memory Stop and dual plugged accessory ports.

QUANTITY	SIZE	GPM	TAG