


3-Way ATCV on Return, (Normally Closed Mixing), 2.0" or smaller, Manual Balanced, Ball Valve Supply, Components: 2x BBe, UB & MBe



**MODEL UB**

UB Union is an O-ring sealed union with two 0.25" plugged accessory ports. Fixed End Connections available in FNPT or SWT. Tailpiece Connections available in MNPT, FNPT or SWT. Size reductions available. Shown with "PV" Combination Manual Air Vent and Pressure/ Temperature Port.

**MODEL MBe**

MB Manual Balancing Valve is a venturi balancing and shut off valve. Accuracy  $\pm 3\%$  of flow rate. Fixed End connection available in FNPT or SWT. Tailpiece connection available in MNPT, FNPT or SWT. Size reductions available. Standard features include Adjustable Memory Stop and Dual Pressure/Temperature Ports.

**2x MODEL BBe**

BB Union End Ball Valve is a throttling and shut off valve. Fixed End connection available in FNPT or SWT. Tailpiece connection available in MNPT, FNPT and SWT. Size reductions available. Standard features include Adjustable Memory Stop and dual plugged accessory ports. Supply side shown with "PT" Pressure/ Temperature Port and "DV" Hose End Drain Valve.

QUANTITY	SIZE	GPM	TAG